



WORCRAFT TOOLS
 E-mail: contact@worcraft.uk
 Web: www.worcraft.uk



WORCRAFT[®]
 POWER TOOLS

WORCRAFT 
 POWER TOOLS

WE GOT YOUR TOOLS!





Looking for agent

- No MOQ requirement
- Sufficient stock
- Rapidly delivery



WORCRAFT

POWER TOOLS

10+ YEARS

200+ TOOLS



10.0Ah

2.0Ah

8.0Ah

4.0Ah

6.0Ah

Member of the "WORCRAFT 20V Team" family

LITHIUM
HIGH QUALITY
20V

WE GOT YOUR TOOLS!

<http://www.worcraft.uk>

CHAIN SAW

CGC-S40LiBA

40V



SPECIFICATIONS

Voltage	40V(2x20V)
Bar and Chain	16"(400mm)
Chain Speed	15m/s
Oil reservoir capacity	260ml
SDS: Tool Free Chain Tensioning	
Packing	Color Box



LAWN MOWER

CLM-S40Li

40V



SPECIFICATIONS

Voltage	40V(2x20V)
No load speed	3300 min ⁻¹
Cutting width	13"(340mm)
Front/back wheel	6" / 7"
Height position	6 levels 20-65mm
Capacity of grass bag	35L
Packing	Color Box



LAWN MOWER

CLM-S40LiB

40V



SPECIFICATIONS

Voltage	40V(2x20V)
No load speed	3600 min ⁻¹
Cutting width	16"(400mm)
Front/back wheel	7" / 9"
Height position	6 levels 25-70mm
Capacity of grass bag	45L
Packing	Color Box



BATTERY PACK

CLB-20V-2.0/4.0

V



SPECIFICATIONS

Voltage/Capacity	20V, 2.0 Ah/4.0Ah/6.0Ah
Packing	Color Box

BATTERY PACK

CLB-20V- 6.0

20V



SPECIFICATIONS

Voltage/Capacity	20V, 2.0 Ah/4.0Ah/6.0Ah
Packing	Color Box

NYLON TOOLS BAG

WTFTB-01

600D



SPECIFICATIONS

600D	
Packing	Carton Box



CHARGER WITH LED

CUA-S20Li

0V



SPECIFICATIONS

Voltage	20V
LED Output power	5W
Luminous flux	400Lm
rotation angle	180°
DC Output:	
USB	1A--1PC
Type-C	2A--1PC
Packing	Color Box

BATTERY CHARGER

CLC-20V-4.5

98W



SPECIFICATIONS

Voltage/Frequency	220-240V, 50/60Hz
Rated power	98W
Battery charging voltage	21.5Vd.c.
Charging Current	4.5A
Packing	Color box

BATTERY CHARGER

CLC-20V-2.4H

60W



SPECIFICATIONS

Voltage/Frequency	220-240V, 50/60Hz
Rated power	60W
Battery charging voltage	21Vd.c.
Charging Current	2.4A
Packing	Color box

BATTERY CHARGER

CLC-20V-2.4D

98W



SPECIFICATIONS

Voltage/Frequency	230V-50Hz
Rated power	120W
Battery charging voltage	21.4Vd.c.
Charging Current	2.4Ax2
Packing	Color box

NYLON TOOLS BAG

WTFTB-03

16"



SPECIFICATIONS

600D	
Packing	Carton Box

NYLON TOOLS BAG

WTFTB-04

10"



SPECIFICATIONS

600D	
Packing	Carton Box



VELCRO SANDING PAPER	Model No.	Size	Grit	Q'TY	Using for mdoel	Packing
	WP-I1960-RS	125mm	60	5	CRS-S20Li	Plastic bag with card
	WP-I1980-RS	125mm	80	5	CRS-S20Li	Plastic bag with card
	WP-I19100-RS	125mm	100	5	CRS-S20Li	Plastic bag with card
	WP-I1960-FS	94X185mm	60	5	CPMS-S20Li	Plastic bag with card
	WP-I1980-FS	94X185mm	80	5	CPMS-S20Li	Plastic bag with card
	WP-I19100-FS	94X185mm	100	5	CPMS-S20Li	Plastic bag with card
	WP-I1960-MS	98X140mm	60	5	CFS-S20Li	Plastic bag with card
	WP-I1980-MS	98X140mm	80	5	CFS-S20Li	Plastic bag with card
	WP-I19100-MS	98X140mm	100	5	CFS-S20Li	Plastic bag with card

DIAMOND BLADE	Model No.	D [mm]	d [mm]	b [mm]	Type	Usage
	DM-D22/180-10H	180	22.2	10	Segmented for dry cutting	Cutting for granite, marble and other materials.
	DM-D22/230-10H	230	22.2	10	Segmented for dry cutting	Cutting for granite, marble and other materials.
	DM-T22/125-7H	125	22.2	7	Turbo for dry&wet cutting	Cutting for granite, marble, concrete and other materials.
	DM-T22/180-10H	180	22.2	10	Turbo for dry&wet cutting	Cutting for granite, marble, concrete and other materials.
	DM-T22/230-10H	230	22.2	10	Turbo for dry&wet cutting	Cutting for granite, marble, concrete and other materials.
	DM-W22/110-7H	110	22.2	7	Continuous for wet cutting	Cutting for ceramic tiles as well as thin granite and marble slabs.
	DM-W22/125-10H	125	22.2	10	Continuous for wet cutting	Cutting for ceramic tiles as well as thin granite and marble slabs.
	DM-W22/180-10H	180	22.2	10	Continuous for wet cutting	Cutting for ceramic tiles as well as thin granite and marble slabs.
	DM-W22/230-10H	230	22.2	10	Continuous for wet cutting	Cutting for ceramic tiles as well as thin granite and marble slabs.

TECHNICAL SPECIFICATIONS

ABRASIVE DISC	Model No.	D [mm]	d [mm]	b [mm]	Type	Usage
	GS-F22/115-1H	115	22.2	1	Straight	Cutting for stainless steel
	GS-F22/125-1H	125	22.2	1	Straight	Cutting for stainless steel
	GSC-F22/230-1.9H	230	22.2	1.9	Straight	Cutting for stainless steel
	GS-F22/355-3.2H	355	22.2	3.2	Straight	Cutting for metal
	GS-B22/115-3H	115	22.2	3	Bent at right angle	Cutting for metal
	GS-B22/180-3H	180	22.2	3	Bent at right angle	Cutting for metal
	GS-B22/230-3H	230	22.2	3	Bent at right angle	Cutting for metal
	GS-B22/115-6H	115	22.2	6	Bent at right angle	Grinding for metal & stone
	GS-B22/230-6H	230	22.2	6	Bent at right angle	Grinding for metal & stone
	GSC-F22/115-3H	115	22.2	3	Straight	Cutting for stone
	GSC-F22/125-3H	125	22.2	3	Straight	Cutting for stone
	GSC-F22/180-3H	180	22.2	3	Straight	Cutting for stone
	GSC-F22/230-3H	230	22.2	3	Straight	Cutting for stone

Notice*: The technical specifications of each item must correspond to the technical characteristics of the used power tool [RPM, rated power, spindle dimension].

